

Product Specification Information – VCTCXO / TCXO

Available options

Type	package	Supply Voltage (V)	Pulling Range (ppm)	Freq. Stability (ppm)	Temp. Range(°C)	Output Logic and Symmetry	Oscillator Mode	Appearance	Lead Free	Dash	Freq. (MHz)
T: TCXO	Y: 2.5 x 2.0 X: 3.2 x 2.5 V: 5.0 x 3.2 C: 7.0 x 5.0 S: 7.0 x 5.0 K: 14.3 x 8.7	C: 5.0 E: 2.8~3.3 J: 2.4~2.7 K: 1.8 (TY only)	A: ± 5 B: ± 8 C: ±10 T: TCXO Vcon range: 0.5V to 2.5V	A: ±0.5 B: ±1.0 P: ±1.5 C: ±2.0 D: ±2.5 E: ±3.0 F: ±4.0 G: ±5.0 T:±4.6 (Including 20 Years Aging)	I: -10~+60 C: -20~+70 L: -40~+85 D: -30~+85	50±5% A 10 TTL 15pF J CMOS 15pF F CMOS 50 pF S: Clipped sine wave @ 10 KΩ/10pF	-A:AT Fundamental Not selectable by customer	S:For Stratum 3 N :Normal T:With Tri-State	F: RoHs Compliant		XX.XXX
	F: 20.4x12.8 (Dip) G: 20.0x13.0	Gull wing G: 5.0 F: 2.8~3.3 Through Hole T: 5.0 E: 2.8~3.3		W: 0~+55 I: 0~+70 C: -10~+60 E: -20~+70 H: -30~+75 U: -40~+85							

T X E C D D S A N F – 26

*Not all combinations of options are available.

Example: TXECDDSANF-26

Type	TCXO
Package	3.2 x 2.5 mm
Supply Voltage(V)	3.3 V
Pulling Range	±10 ppm
Freq. Stability	±2.5 ppm
Temp Range	-30~+85 °C
Output	Clipped sine wave
Oscillator Mode	AT Fundamental
Appearance	Normal Appearance
Lead Free	RoHs Compliant
Frequency	26 MHz