

Product Specification Information – OCXO

Available options

Type	Package (mm)	Supply Voltage (V)	Pulling Range (ppm)	Freq. Stability (ppb)	Temp. Range(°C)	Output Logic and Symmetry		Oscillator Mode	Pin out	Lead Free	Dash	Freq. (MHz)
N: OCXO	A: 25.4 x 25.4 J: 25.4 x 22.1 I: 36.3 x 27.2 B: 50.8 x 50.8 F: 20.4 x 12.8	A: 12.0 E: 3.3 T: 5.0	K: ±0.2 H: ±0.4 D: ±1.0 G: ±3.0 E: ±5.0 N: NC	R: ±2 A: ±5 B: ±10 C: ±20 E: ±30 G: ±50 N: NC	B: 0~+50 E: 0~+70 D: -30~+70		50±10%	Not selectable by customer	N : Normal A : Optional (Please refer to "outline drawing")	F: RoHs Compliant		XX.XXX
						J	CMOS 15pF					
						W	Sine wave					

N A T H C E W H N F – 10

Example: NATHCEWHNF-10

Type	OCXO
Package	25.4 x 25.4 mm
Supply Voltage(V)	5 V
Pulling Range	±0.4 ppm
Freq. Stability	±20 ppb
Temp Range	0~+70 °C
Output	Sine wave
Pin Out	Normal
Lead Free	RoHs Compliant
Frequency	10 MHz

*Not all combinations of options are available.